

Generics

A major part of software engineering is building components that not only have well-defined and consistent APIs, but are also reusable. Components that are capable of working on the data of today as well as the data of tomorrow will give you the most flexible capabilities for building up large software systems.

In languages like C# and Java, one of the main tools in the toolbox for creating reusable components is *generics*, that is, being able to create a component that can work over a variety of types rather than a single one. This allows users to consume these components and use their own types.

Hello World of Generics

To start off, let's do the "hello world" of generics: the identity function. The identity function is a function that will return back whatever is passed in. You can think of this in a similar way to the echo command.

Without generics, we would either have to give the identity function a specific type:

```
function identity(arg: number): number {  
    return arg;  
}
```

Or, we could describe the identity function using the any type:

```
function identity(arg: any): any {  
    return arg;  
}
```

Instead, we need a way of capturing the type of the argument in such a way that we can also use it to denote what is being returned. Here, we will use a *type variable*, a special kind of variable that works on types rather than values.

```
function identity<T>(arg: T): T {  
    return arg;  
}
```

We've now added a type variable `T` to the `identity` function. This `T` allows us to capture the type the user provides (e.g. `number`), so that we can use that information later. Here, we use `T` again as the return type. On inspection, we can now see the same type is used for the argument and the return type. This allows us to traffic that type information in one side of the function and out the other.

We say that this version of the `identity` function is generic, as it works over a range of types. Unlike using `any`, it's also just as precise (ie, it doesn't lose any information) as the first `identity` function that used numbers for the argument and return type.

Once we've written the generic `identity` function, we can call it in one of two ways. The first way is to pass all of the arguments, including the type argument, to the function:

```
let output = identity<string>("myString");  
//      ^ = let output: string
```

Here we explicitly set `T` to be `string` as one of the arguments to the function call, denoted using the `<>` around the arguments rather than `()`.

The second way is also perhaps the most common. Here we use *type argument inference* — that is, we want the compiler to set the value of `T` for us automatically based on the type of the argument we pass in:

```
let output = identity("myString");  
//      ^ = let output: string
```

may need to explicitly pass in the type arguments as we did in the previous example when the compiler fails to infer the type, as may happen in more complex examples.

Working with Generic Type Variables

When you begin to use generics, you'll notice that when you create generic functions like `identity`, the compiler will enforce that you use any generically typed parameters in the body of the function correctly. That is, that you actually treat these parameters as if they could be any and all types.

Let's take our `identity` function from earlier:

```
function identity<T>(arg: T): T {  
    return arg;  
}
```

What if we want to also log the length of the argument `arg` to the console with each call? We might be tempted to write this:

```
function loggingIdentity<T>(arg: T): T {  
    console.log(arg.length);  
    Property 'length' does not exist on type 'T'.  
    return arg;  
}
```

When we do, the compiler will give us an error that we're using the `.length` member of `arg`, but nowhere have we said that `arg` has this member. Remember, we said earlier that these type variables stand in for any and all types, so someone using this function could have passed in a number instead, which does not have a `.length` member.

Let's say that we've actually intended this function to work on arrays of `T` rather than `T` directly. Since we're working with arrays, the `.length` member should be available. We can describe this just like we would create arrays of other types:

```
let myStringArray: string[] = ['hello', 'world'];  
let myNumberArray: number[] = [1, 2, 3];  
let myBooleanArray: boolean[] = [true, false];  
let myAnyArray: any[] = [1, 'hello', true];  
let myUnknownArray: unknown[] = [1, 'hello', true];  
let myNeverArray: never[] = [];
```

Search Docs

Docs

Community

Tools

You can read the type of `loggingIdentity` as “the generic function `loggingIdentity` takes a type parameter `T`, and an argument `arg` which is an array of `T`s, and returns an array of `T`s.” If we passed in an array of numbers, we’d get an array of numbers back out, as `T` would bind to `number`. This allows us to use our generic type variable `T` as part of the types we’re working with, rather than the whole type, giving us greater flexibility.

We can alternatively write the sample example this way:

```
function loggingIdentity<T>(arg: Array<T>): Array<T> {  
    console.log(arg.length); // Array has a .length, so no more error  
    return arg;  
}
```

You may already be familiar with this style of type from other languages. In the next section, we’ll cover how you can create your own generic types like `Array<T>`.

Generic Types

In previous sections, we created generic identity functions that worked over a range of types. In this section, we’ll explore the type of the functions themselves and how to create generic interfaces.

The type of generic functions is just like those of non-generic functions, with the type parameters listed first, similarly to function declarations:

```
function identity<T>(arg: T): T {  
    return arg;  
}  
  
let myIdentity: <T>(arg: T) => T = identity;
```

We could also have used a different name for the generic type parameter in the type, so long as the number of type variables and how the type variables are used line up.

```
let myIdentity: <U>(arg: U) => U = identity;
```

We can also write the generic type as a call signature of an object literal type:

```
function identity<T>(arg: T): T {  
    return arg;  
}  
  
let myIdentity: { <T>(arg: T): T } = identity;
```

Which leads us to writing our first generic interface. Let's take the object literal from the previous example and move it to an interface:

```
interface GenericIdentityFn {  
    <T>(arg: T): T;  
}  
  
function identity<T>(arg: T): T {  
    return arg;  
}  
  
let myIdentity: GenericIdentityFn = identity;
```

In a similar example, we may want to move the generic parameter to be a parameter of the whole interface. This lets us see what type(s) we're generic over (e.g. `Dictionary<string>` rather than just `Dictionary`). This makes the type parameter visible to all the other members of the interface.

```
interface GenericIdentityFn<T> {  
    (arg: T): T;  
}  
  
function identity<T>(arg: T): T {
```

Search Docs

Docs

Community

Tools

Notice that our example has changed to be something slightly different. Instead of describing a generic function, we now have a non-generic function signature that is a part of a generic type. When we use `GenericIdentityFn`, we now will also need to specify the corresponding type argument (here: `number`), effectively locking in what the underlying call signature will use. Understanding when to put the type parameter directly on the call signature and when to put it on the interface itself will be helpful in describing what aspects of a type are generic.

In addition to generic interfaces, we can also create generic classes. Note that it is not possible to create generic enums and namespaces.

Generic Classes

A generic class has a similar shape to a generic interface. Generic classes have a generic type parameter list in angle brackets (`<>`) following the name of the class.

```
class GenericNumber<T> {
  zeroValue: T;
  add: (x: T, y: T) => T;
}

let myGenericNumber = new GenericNumber<number>();
myGenericNumber.zeroValue = 0;
myGenericNumber.add = function (x, y) {
  return x + y;
};
```

This is a pretty literal use of the `GenericNumber` class, but you may have noticed that nothing is restricting it to only use the `number` type. We could have instead used `string` or even more complex objects.

```
// @strict: false
class GenericNumber<T> {
  zeroValue: T;
  add: (x: T, y: T) => T;
```

Search Docs

Docs

Community

Tools

```
stringNumeric.add = function (x, y) {  
    return x + y;  
};  
  
console.log(stringNumeric.add(stringNumeric.zeroValue, "test"));
```

Just as with interface, putting the type parameter on the class itself lets us make sure all of the properties of the class are working with the same type.

As we covered in [our section on classes](#), a class has two sides to its type: the static side and the instance side. Generic classes are only generic over their instance side rather than their static side, so when working with classes, static members can not use the class's type parameter.

Generic Constraints

If you remember from an earlier example, you may sometimes want to write a generic function that works on a set of types where you have some knowledge about what capabilities that set of types will have. In our `loggingIdentity` example, we wanted to be able to access the `.length` property of `arg`, but the compiler could not prove that every type had a `.length` property, so it warns us that we can't make this assumption.

```
function loggingIdentity<T>(arg: T): T {  
    console.log(arg.length);  
    Property 'length' does not exist on type 'T'.  
    return arg;  
}
```

Instead of working with any and all types, we'd like to constrain this function to work with any and all types that also have the `.length` property. As long as the type has this member, we'll allow it, but it's required to have at least this member. To do so, we must list our requirement as a constraint on what `T` can be.

To do so, we'll create an interface that describes our constraint. Here, we'll create an

```
interface Lengthwise {
  length: number;
}

function loggingIdentity<T extends Lengthwise>(arg: T): T {
  console.log(arg.length); // Now we know it has a .length property
  return arg;
}
```

Because the generic function is now constrained, it will no longer work over any and all types:

```
loggingIdentity(3);

Argument of type 'number' is not assignable to parameter of type 'Lengthwise'.
```

Instead, we need to pass in values whose type has all the required properties:

```
loggingIdentity({ length: 10, value: 3 });
```

Using Type Parameters in Generic Constraints

You can declare a type parameter that is constrained by another type parameter. For example, here we'd like to get a property from an object given its name. We'd like to ensure that we're not accidentally grabbing a property that does not exist on the obj, so we'll place a constraint between the two types:

```
function getProperty<T, K extends keyof T>(obj: T, key: K) {
  return obj[key];
}
```

```
1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100
```

Search Docs

Docs

Community

Tools

Argument of type '"m"' is not assignable to parameter of type '"a" | "b" | "c" | "d"'.

Using Class Types in Generics

When creating factories in TypeScript using generics, it is necessary to refer to class types by their constructor functions. For example,

```
function create<T>(c: { new (): T }): T {  
    return new c();  
}
```

A more advanced example uses the prototype property to infer and constrain relationships between the constructor function and the instance side of class types.

```
class BeeKeeper {  
    hasMask: boolean;  
}  
  
class ZooKeeper {  
    nametag: string;  
}  
  
class Animal {  
    numLegs: number;  
}  
  
class Bee extends Animal {  
    keeper: BeeKeeper;  
}  
  
class Lion extends Animal {  
    keeper: ZooKeeper;  
}  
  
function createInstances<A extends Animal>(c: new () => A): A {
```

Search Docs

```
createInstance(Lion).keeper.nametag;  
createInstance(Bee).keeper.hasMask;
```

Previous



Enums

How TypeScript enums work

The TypeScript docs are an open source project. Help us improve these pages [by sending a Pull Request](#) ❤️

Contributors to this page:



DR OT MH

RC 13+

Last updated: Dec 28, 2020

This page loaded in 3.335 seconds.

Customize

Site Colours:

Popular Documentation Pages

Basic Types

JavaScript primitive types inside TypeScript

Interfaces

How to provide a type shape to JavaScript objects

TSConfig Options

Configuration options for TypeScript

Advanced Types

TypeScript language extensions to JavaScript

Variable Declarations

How to create and type JavaScript variables

Classes

How to provide types to JavaScript ES6 classes

Functions

How to provide types to functions in JavaScript

TypeScript in 5 minutes

An overview of building a TypeScript web app

Search Docs

Docs

Community

Tools

Community Chat
Web Updates
Using TypeScript

@TypeScript
Web Repo

Download

TSConfig Ref
▼ Code Samples

Stack Overflow

Community

Why TypeScript

Made with ♥ in Redmond,
Boston, SF & Dublin

© 2012-2021 Microsoft
Privacy

Search Docs

Docs

Community

Tools